

# STERLING MODEL "GG" LOW PROFILE TUBULAR DESIGN GAS FIRED UNIT HEATER

---

## STANDARD FEATURES

- Up to 82%+ Thermal Efficiency
- Redundant Single Stage Gas Valve
- Residential Certification
- 20GA Aluminized Heat Exchanger
- 120/24V Control Transformer
- 115/1/60 Fan Motor with Internal Overload Protection
- Power Vented
- Direct Spark Ignition
- 20GA Baked Enamel Cabinet
- 10 Year Heat Exchanger Warranty
- OSHA Fan Guard
- Right Hand Control Access
  - Field Convertible to Left Hand
- High Limit Switch
- Air Pressure Switch
- Natural or Propane Gas
- Gas Conversion Kit Included
- Field Convertible to Separated Combustion
- Easy Access Control Panel
- 321 Stainless Steel Burner Box

## OPTIONAL EQUIPMENT

- 409 Stainless Steel Heat Exchanger
- Two Stage Gas Control (Sizes 60-120 Only)
- Supply Voltage (Field Mounted Transformers):
  - 208/1/60
  - 230/1/60
  - 208/3/60
  - 230/3/60
  - 460/3/60
  - 575/3/60
- Totally Enclosed Motors (Sizes 60-120 Only)
- Stainless Steel Flue Collector
- Pressure Regulator (1/2 – 2 psi)
- Single & Two Stage Mercury Free Thermostats
- Line Volt Thermostat
- Locking Thermostat Cover
- 24V SPST Relay
- Vent Caps
- Concentric Vent Kits  
(For All Separated Combustion Installations)

January 7, 2014  
(Exhibit #10)



**STERLING**<sup>®</sup>

HVAC PRODUCTS



