



March 2, 2016

Honorable Wayne Shaw
Brown County Commissioner
200 South Broadway St.
Brownwood, TX 76665

Dear Wayne,

Confirming our conversation today, we are pleased to offer the following quotation:

UPM® High Performance Asphalt Repair \$ 88.00/ton FOB Bridgeport, TX
\$120.00 delivered to your yard
Available with 1 day notice for pick up. Delivery: 2 days after order.
Terms: Net 30 days.

This is in response to your request for Cold Mix bid. UPM is not conventional cold mix but is rather a permanent repair product. I appreciate your recent orders and look forward to furnishing you with the same "Good Stuff" in the future.

Sincerely,

A handwritten signature in black ink, appearing to read "LeVan Reber", written in a cursive style.

LeVan Reber
Account Executive

March 14, 2016
(Exhibit #3)

**BROWN COUNTY
BID SPECIFICATIONS
FOR CRUSHED CALICHE, CRUSHED LIMESTONE,
COVER ROCK AND COLD MIX**

Crushed Base Material (1 3/4" and below)

Oversized Rock (3" X 5")

Grade 4 and Grade 5 Cover Rock

Cold Mix — *UPM High Performance Cold Patch*

All priced per yard and loaded on truck



The Good Stuff®

The Standard in Permanent Pavement Repair



User Recommendations

Store on a clean hard surface to avoid contamination.

Stack in a single rectangular-shaped pile to minimize the exposed surface.

Stir and load from one point, mixing the crust with material from below.

Do not freshen up UPM stockpiles by turning the stockpile. Mix only enough for immediate use. Stirring the excess material will dry out the mix and shorten stockpile life.

Place material in area being repaired in 1-2" lifts and compact individual lifts. Larger repair areas may require a dusting of Portland cement or sand between lifts for increased stability.

Do not use any petroleum products, as contact with them will break down the properties of the UPM.

UPM can be used in a hotbox at temperatures not to exceed 90 degrees Fahrenheit.

UPM is self-priming and does not require any use of tack for bonding.

Remove loose debris from the area being repaired. Use broom or other device to remove loose debris prior to filling. Water in the hole has no effect on performance of UPM. Remove or melt ice.

Compact, Compact, Compact! Use hand tamper, vibratory compactor, roller or vehicle tire to compact UPM. UPM will compact approximately 25%.

Unlike other cold mix, UPM doesn't need to be removed before hot mix is applied.



UPM® is a U.S. Trademark of Unique Paving Materials

Corporate Office | 3993 E. 93rd Street | Cleveland, OH 44105 | 800.441.4880 | UniquePavingMaterials.com

Unique Paving Materials
3993 East 93rd Street
Cleveland, Ohio 44105-4096

CRUSHED Rock BID
Brazil Quarry Area
200 S. Brannan #101
Brownsville TX 76861

FILED FOR RECORD
TIME 3:57 pm

MAR 8 2016

Sharon Ferguson, Brown County Clerk
Deputy D. Walders